



- A- \_\_\_\_\_ INSIDE BORE
- B- \_\_\_\_\_ BOLT CIRCLE
- C- \_\_\_\_\_ 'T'-STYLE
- C- \_\_\_\_\_ 'L'-STYLE
- D- \_\_\_\_\_ THICKNESS
- E- \_\_\_\_\_ SHOULDER
- F- \_\_\_\_\_ DIA. \_\_\_\_\_ BOLT \_\_\_\_\_ HOLE (CHECK ONE)
- G- \_\_\_\_\_ NUMBER OF HOLES
- H- ARE HOLES EQUALLY SPACED? \_\_\_\_\_
- J- NUMBER OF TEETH \_\_\_\_\_
- K- CHAIN NUMBER AND BRAND \_\_\_\_\_

**Reliable ENGINE ASPHALT Products**  
 P.O. Box 519 Shelbyville KY 40066  
 Phone: (502) 647-1782 Fax: (502) 647-1786

SCALE: NONE APPROVED BY: \_\_\_\_\_ DRAWN BY: Todd  
 JOB: FILL IN DATE: 10/25/05

**SEGMENTED "SPROCKET"  
 CUSTOMER "FILL IN"**

**RAP STANDARD** DRAWING NUMBER \_\_\_\_\_ SEGMENTED SPROCKET

REV	BY	DATE	DESCRIPTION
			TOLERANCES UNLESS OTHERWISE NOTED
			FRACTIONAL DIM. $\pm 1/16"$ ANGULAR DIM. $\pm 1/2^\circ$
			DECIMAL DIM. $\pm .000$
			COO $\pm .005$
			COO $\pm .005$

THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO RELIABLE ASPHALT PRODUCTS AND SHALL NOT BE REPRODUCED OR DISCLOSED IN WHOLE OR IN PART, NOR USED FOR ANY DESIGN OR MANUFACTURING PURPOSE UNLESS AUTHORIZED IN WRITING BY RELIABLE ASPHALT PRODUCTS.

1 - T'-STYLE

2 - L'-STYLE